

ENSTO

HIT3.1204L

Heat shrink indoor termination

Code	HIT3.1204L
GTIN	6418677444463
ENumber	
Name	Heat shrink indoor termination 6/10 (12) kV Al/Cu 150-300 mm ² 3 core with lugs
Description	The termination kit is used for indoor terminating of max. 12 kV cables with XLPE insulation and copper wire shield. The kit is suitable for three core cables. The kit includes the shear head bolt cable lugs suitable both for aluminium and copper conductors, and all the components needed for terminating: a shear head bolt cable lug for the cable wire shield, mastics, tapes, cleaning and grinding materials, heat shrink stress control tubes, insulating anti-tracking breakout and tubes.



Technical specification

Dimensions

Conductor size:	Al/Cu 150-300
Shield size mm ² :	Al/Cu 6-50
Creepage distance:	650 mm
Termination length L:	500 ... 1100 mm

Features

Accessory type:	Termination, indoor
Shrink technology:	Heat shrink

Ratings

ETIM class:	EC000910
-------------	----------

Cable Features

Insulation material:	Plastic
----------------------	---------

Screen/Shield material: Cu-wire

No. of cores: 3

ETIM

ETIM

Model: Heat-shrink

Voltage row: 6/10 kV

Nominal cross section: 150 ... 300 mm²

Number of conductors: 3