

# ENSTO

## HJW11.2402C

### Heat shrink joint

Code	HJW11.2402C
GTIN	6418677447051
ENumber	
Name	Heat shrink joint 12/20 (24) kV Al/Cu 25-95 mm <sup>2</sup> AHXAMK-W 3x1 core with connectors
Description	The joint kit is used for jointing of max. 24 kV cables with XLPE insulation and aluminium tape shield. The kit is suitable for AHXAMK-W cables, containing the components for three cores. The kit includes the shear head bolt cable connectors suitable for both aluminium and copper conductors, and all the components needed for jointing: mastics, tapes, cleaning and grinding materials, heat shrink stress control tubes, insulating and semiconductive tubes as well as sealing tubes. The kit contains also tubular Cu-wire braids and constant force springs for shielding of the joint and a connector to join the cable earth conductor.



## Technical specification

### Dimensions

<b>Weight:</b>	5.87 kg
<b>Conductor size 24 kV:</b>	Al/Cu 25-95
<b>Length:</b>	800 mm
<b>Conductor size 12 kV:</b>	Al/Cu 50-95
<b>Shield size mm<sup>2</sup>:</b>	3 x Cu 25
<b>Nominal cross section:</b>	25 ... 95 mm <sup>2</sup>

### Features

<b>Accessory type:</b>	Straight through joint
<b>Shrink technology:</b>	Heat shrink

## Ratings

**ETIM class:** EC001169

## Cable Features

**Insulation material:** Plastic

**Screen/Shield material:** Al-laminate

**No. of cores:** 3

## ETIM

---

### ETIM

**Model:** Heat-shrink

**Halogen free:** true

**Voltage row:** 12/20 kV

**Number of conductors:** 3

**Nominal cross section conductor:** 25 ... 95 mm<sup>2</sup>

**With concentric shielding:** true

## Packaging

---

### Default package

**Unit:** PCS