

ENSTO

HJW11.2403C

Heat shrink joint with connector

Code	HJW11.2403C
GTIN	6418677447068
ENumber	
Name	Heat shrink joint with connector 12/20 (24) kV Al/Cu 70-240 mm ² AHXAMK-W 3x1 core with connectors
Description	The joint kit is used for jointing of max. 24 kV cables with XLPE insulation and aluminium shield. The kit is suitable for AHXAMK-W cables, containing the components for three cores. The kit includes the shear head bolt cable connectors suitable for both aluminium and copper conductors, and all the components needed for jointing: mastics, tapes, cleaning and grinding materials, heat shrink stress control tubes, insulating and semiconductive tubes as well as sealing tubes. The kit contains also tubular Cu-wire braids and constant force springs for shielding of the joint and a connector to join the cable earth conductor.



Technical specification

Dimensions

Weight:	6.69 kg
Conductor size 24 kV:	Al/Cu 70-240
Length:	800 mm
Conductor size 12 kV:	Al/Cu 120-240
Shield size mm²:	3 x Cu 25
Nominal cross section:	70 ... 240 mm ²

Features

Accessory type:	Straight through joint
Shrink technology:	Heat shrink

Ratings

ETIM class: EC001169

Cable Features

Insulation material: Plastic

Screen/Shield material: Al-laminate

No. of cores: 3

ETIM

ETIM

Model: Heat-shrink

Halogen free: true

Voltage row: 12/20 kV

Number of conductors: 3

Nominal cross section conductor: 70 ... 240 mm²

With concentric shielding: true

Packaging

Default package

Unit: PCS