

ENSTO

PSS85.5

Copper bar

Code	PSS85.5
GTIN	6418677401367
ENumber	
Name	Copper bar 15 and 22 mm, size 250 mm ²
Description	Used together with busbar connectors to connect Cu- and Al-conductors to high or low voltage transformer bushings. The copper bar PSS 85.5 Is for one connector.



Technical specification

Dimensions

Weight:	0.27 kg
Busbar cross-sectional area:	250 mm ²
Diameter max/min:	22/14

Electrical values

Max. current:	600 A
---------------	-------

Features

For connector:	KG6, KG16, KG41, KG43, KG44, KG20
----------------	-----------------------------------

Ratings

ETIM class:	EC001522
-------------	----------

ETIM

ETIM

Width:	50 mm
Length:	133 mm
Height:	5 mm
Model:	Flat
Rated current In:	600 A

Packaging

Default package

Size:	50
Length:	220 mm
Width:	220 mm
Height:	125 mm
Weight (net):	13.3 kg
Weight (brt):	13.478 kg
Volume:	0.0061

Pallet package

Size:	5250
Length:	1200 mm
Width:	800 mm
Height:	890 mm
Weight (net):	1396.5 kg
Weight (brt):	1417 kg
Volume:	0.8544