

# ENSTO

## SABP081313G

### Cubo S enclosure

|             |   |
|-------------|---|
| Code        | SABP081313G   |
| GTIN        | 6418677155161   |
| ENumber     |   |
| Name        | Cubo S enclosure Ensto Cubo S<br>Size 75 x 125 x 125 mm, 50 mm base, plain sides, grey cover, ABS   |
| Description | Ensto Cubo S is a series of small to medium size enclosures available with knockouts or plain sides. The base of the enclosures is equipped with unique slots for printed circuit boards. |



## Technical specification

### Technical specification

|                 |  |
|-----------------|--|
| <b>Content:</b> | Enclosure base, cover, cover screws, mounting screws |
|-----------------|--|

### Dimensions

|                            |                |
|----------------------------|----------------|
| <b>Weight:</b>             | 0.27 kg        |
| <b>Width:</b>              | 75 mm          |
| <b>Size:</b>               | 75 x 125 x 125 |
| <b>Height:</b>             | 125 mm         |
| <b>Depth:</b>              | 125 mm         |
| <b>Inner depth:</b>        | 110.5 mm       |
| <b>Outer base depth:</b>   | 50 mm          |
| <b>Outer cover height:</b> | 75 mm          |

### Temperatures

|                                      |                |
|--------------------------------------|----------------|
| <b>Operating temperature:</b>        | -40 ... +60 °C |
| <b>Short term temperature range:</b> | -40 ... +80 °C |

### Materials

|               |     |
|---------------|-----|
| <b>Base:</b>  | ABS |
| <b>Cover:</b> | ABS |

|                            |              |
|----------------------------|--------------|
| <b>Cover screws:</b>       | Polyamide    |
| <b>Gasket:</b>             | Polyurethane |
| <b>Material selection:</b> | ABS          |

## Colors

|               |      |
|---------------|------|
| <b>Color:</b> | Grey |
|---------------|------|

## Mechanical

|                         |             |
|-------------------------|-------------|
| <b>Impact strength:</b> | IK 07/IK 06 |
|-------------------------|-------------|

## Certificates

|                   |                  |
|-------------------|------------------|
| <b>Standards:</b> | EN 62208, GOST R |
|-------------------|------------------|

## Ratings

|                              |           |
|------------------------------|-----------|
| <b>Degree of protection:</b> | IP66/IP67 |
| <b>ETIM class:</b>           | EC000261  |

## ETIM

---

### ETIM

|                                     |           |
|-------------------------------------|-----------|
| <b>Width:</b>                       | 75 mm     |
| <b>Colour:</b>                      | Grey      |
| <b>Material:</b>                    | Plastic   |
| <b>Height:</b>                      | 125 mm    |
| <b>Depth:</b>                       | 125 mm    |
| <b>Type of surface:</b>             | Untreated |
| <b>RAL-number:</b>                  | 7035      |
| <b>Wall fastening possible:</b>     | true      |
| <b>Suitable for outdoor set-up:</b> | false     |
| <b>Impact strength:</b>             | IK06      |
| <b>Degree of protection (IP):</b>   | IP67      |
| <b>With mounting plate:</b>         | false     |
| <b>With glazed door:</b>            | false     |

## Packaging

---

### Default package

|                      |          |
|----------------------|----------|
| <b>Unit:</b>         | PCS      |
| <b>Size:</b>         | 9        |
| <b>Length:</b>       | 375 mm   |
| <b>Width:</b>        | 250 mm   |
| <b>Height:</b>       | 157 mm   |
| <b>Weight (net):</b> | 0.267 kg |
| <b>Weight (brt):</b> | 2.661 kg |
| <b>Volume:</b>       | 14.71875 |