

ENSTO

SH154

CC vertical angle crossarm

Code	SH154
GTIN	6418677406850
ENumber	
Name	CC vertical angle crossarm 20 kV, A=550
Description	For suspending single, three phase covered conductor line. Allowed loads for the crossarm at conductor fixing points are: $F_x=14.0$ kN angle load, $F_z=4.5$ kN horizontally along conductor, $F_y=4.0$ kN vertically downwards.

Technical specification

Dimensions

Weight:	5.1 kg
Pole diameter:	≤ 225 mm

Electrical values

Voltage:	20 kV
----------	-------

Drawing markings

L:	250 mm
A:	550 mm
E:	24 mm
d:	M20
K:	≥ 70 mm

Mechanical

Allowed loads at conductor fixing point:	$F_x = 14.0$, $F_z = 4.5$ kN, $F_y = 4.0$ kN
--	---

Packaging

Default package

Unit:	PCS
Size:	5

Length:	600 mm
Width:	260 mm
Height:	210 mm
Weight (net):	25.5 kg
Volume:	0.0328

Pallet package

Unit:	PCS
Size:	120
Length:	1200 mm
Width:	800 mm
Height:	990 mm
Weight (net):	612 kg
Weight (brt):	632 kg
Volume:	0.9504